

For More Information

visit www.KitchenBrains.com,
email sales@kitchenbrains.com or contact
us via the phone numbers below.

Kitchen Brains® Corporate Office

905 Honeyspot Road
Stratford, CT 06615-7147 USA
Phone: +1-203-377-4174

UK

31 Saffron Court, Southfields Business Park
Basildon Essex SS15 6SS
Phone: +44 (0) 1268 544000

China

1803, 18F, No 922 Hengshan Road
Shanghai 200030, CHINA
Phone: +8613916 854 613

Asia Pacific

13A MacKenzie Road
228676 Singapore
Phone: +65 98315927



PRODUCT LINE GUIDE



KITCHEN BRAINS®
(FAST) MODULARM SCK



KITCHEN BRAINS®
(FAST) MODULARM SCK

The Time is Right

PUT A GENIUS ON THE MENU



As a leading manufacturer of refrigeration monitoring devices, the Kitchen Brains® Modularm® product line is designed to protect perishables, save energy, and increase operator safety.

MODULARM®

75LC Multi-Monitor




Temperature Alarm
Door Ajar Alarm
AC Failure Alarm
Panic Alarm
Automatically adjusts alarm set points
Surface or Flush Mount

DL-35

Provides visual and audible alarm
Field adjustable door monitor settings
Automatic control of interior lights
Replaces ordinary light switches and fan shutoff switches



DAC-55



Provides visual and audible alarm with remote notification
Field adjustable freezer door alarm/door monitor settings
Automatic control of interior lights
Automatic control of refrigeration

75LC Communicator

Rechargeable back-up battery with built-in recharging
Logs historical reports of temperature conditions
Weekly or monthly status updates via email
On-demand report generation with built-in graphing
LCD display for visual system status
Built-in dry contacts and audible alarms
Intuitive web-based operating software
Voice notification of alarm conditions
Security password protected
Hardwired or Wireless



Datalarm



Autoset™ adjusts set points accordingly
Built-in flash memory
Audible, visual and remote alarm notification
Built-in power supply/battery back-up
Easy manual programming
Surface or Flush Mount
25 foot temp sensor leads

RM-200

Ethernet, Wi-Fi, or GPRS
3ft, 6ft, or 20ft Temp Sensor
3ft, 6ft, or 20ft Door Switch Sensor
Mounted



IP-1

Panic alarm
Entrapment alarm
Light/refrigeration control capabilities
Works with: DAC-55, DL-35, and 75LC Models



Model 75

Audible and visual alarm with remote notification
Built-in power supply/battery back-up
High and Low alarm set points
F and C temperature display
Surface or Flush Mount
25' temp sensor



MD-1



Hands free occupancy detection
Low voltage wiring to your 75LC
Lighting control