

Modularm Accessories

PRODUCTS FOR EXPANDING SYSTEM CAPABILITIES

Remote Notification:

All Modularm systems offer audible and visual on-premise alarms and also provide remote notification capability. To facilitate remote annunciation, the following accessories are offered:

Automatic Telephone Dialer

For off-premise alarm annunciation without the monthly monitoring fee of a central station.

- Turn-key system for remote notification.
- Works with existing phone line or a dedicated phone line.
- Easy installation. Requires standard 120VAC outlet, phone jack and connection to alarm.
- Completely solid state.
- Field programmable with up to four telephone numbers for voice/pager operation.
- Field programmable outgoing voice message (16 seconds max.)
- Tone/Pulse dialing.
- Rechargeable battery backup with recharging circuitry for power failure operation.
- Painted steel enclosure.
- Dimensions: 12" x 12" x 3", Weight: 11 lbs.



Custom Remote Annunciator Panel

For when annunciation from a number of individual alarms to a secondary centralized location is desired. (Guard Booth, Manager's Office, etc.)



Custom Remote Annunciator Panel.
Model 24 Alarm is also shown for single point remote annunciation.

- Provides individual visual alarm indicator for each monitored point to easily identify the malfunctioning compartment.
- Provides audible alarm and remote notification capability.



Custom Remote Annunciator Panel and Auto Dialer may be integrated into a single enclosure as shown.

- Custom configured for the number of points being monitored.
- Rechargeable battery backup with recharging circuitry for power failure operation.
- Painted steel enclosure.
- Dimensions: 12" x 12" x 3"
Weight: 10 lbs.



MODULARM CORPORATION

Modularm Accessories

PRODUCTS FOR EXPANDING SYSTEM CAPABILITIES.

Weathertight Enclosure

- Fiberglass reinforced polyester enclosure.
- Bonded 6" x 8" Lexan window for viewing temperature readout and compartment status indicators.
- Stainless steel piano hinge with padlock latch.
- Rubber gasket on door for weather-tight seal.
- External horn mounted on bottom of enclosure for audible alarm annunciation.
- Additional audible and visual alarm devices may be externally mounted for increased annunciation range.
- Suitable for environments from -40F (-40C) to 140F (60C).
- Dimensions: 11"H x 9" W x 5.5" D. Enclosure weight: 5 lbs.

For outdoor installations and harsh or wet environments. Also suitable for tamper proof applications such as correctional institutions.



Shown with Model 75B Temperature Alarm. Other sized enclosures are also available.

Illuminated Pushbutton Switch

(Part #IP-1)

For alarm/control functions from **inside** of the monitored compartment.



- Optional accessory for the **DAC-55 Door Monitor**. (Provides **Panic Alarm** & **Auto Panic Alarm** capability as well as other control functions.)
- Optional accessory for the **Model 24 Alarm**. (Provides **Panic Alarm** capability.)
- Low voltage illumination makes button easy to locate.
- Suitable for environments from -67F(-55C) to 149F (65C).
- Mounted on an appropriately labeled stainless steel faceplate.
- Surface mount in optional enclosure as shown, (Part #SM-1), or flush mount into a standard single gang outlet box.

Bells & Whistles

Modularm is your source for a wide range of annunciation devices. We can provide many types of annunciators including horns, strobe lights, bells and sirens for virtually any monitoring requirement. Operating voltages from 12VDC to line voltage are available and operating environments range from indoor or outdoor use to explosion proof. Let us help you to find the right annunciator for your needs.



Warranty: All systems and components manufactured by Modularm Corporation are warranted to be free from defects in material and workmanship under normal use and service for a period of one year from date of installation. If, during this time period and after examination, any Modularm system or component appears to be defective, Modularm agrees to repair or replace same. This warranty shall not apply to any system or component that has been altered or repaired by anyone other than a factory authorized representative. Modularm Corporation limits this warranty only to those systems and components which it specifically manufactures, and its sole liability shall be to repair or replace these systems and components in accordance with the aforementioned terms, and assumes no additional liabilities. In no case will Modularm's liability exceed the purchase price paid for the product. No other warranty is expressed or implied regarding the sale or use of Modularm system or components.



MODULARM CORPORATION