# **MODULARM Model 75LC Communicator**

Remote Notification & Automatic Data Logging For HACCP Compliance

The **75LC Communicator** is a compact, dedicated system server for up to eight **75LC multi-monitors**. Connection for the 75LCs can be hardwired or wireless with the new 75LC WIreless Module. The 75LC Communicator also serves up to sixteen additional sensors with the new wireless MS-1 multi-sensor.

The 75LC Communicator mounts in a central location such as a manager's office. Linking 75LCs and MS-1s to your computer, computer network or the Internet, the 75LC Communicator harvests data form connected devices and automatically emails historical reports of monitored conditions on a daily or on a weekly basis for help with HACCP compliance. Email and text messages are automatically generated for remote notification, alerting you whenever alarm conditions occur.

### **Features at a Glance**

- Monitors up to eight 75LCs and up to sixteen additional sensors via MS-1s
- Web-based operating software is built right in, no software to install
- Operating software is intuitive and easy to use
- Historical reports of temperature and monitored conditions are automatically created and emailed on a daily or on a weekly basis
- Web-based online viewer is available for viewing historical reports
- Manual, on demand report generation with built-in graphing capability
- Automatic email and text message notification of alarm conditions for remote notification
- Snapshot reports of monitored conditions are viewable on software home page
- Built-in LCD display for visual system status
- Built-in dry contacts and audible alarm provide additional on-premise and remote notification capability
- Rechargeable battery backup with built-in recharging circuitry
- Automatic Telephone Dialer compatible for voice notification of alarm conditions (Additional equipment required)
- Security password protected



ALARM SILENCE

75LC multi-monitor

75LC Communicator

## **Total System Features**

- HI & LO Temperature Alarm
- AC Failure Alarm
- Panic Alarm
- Automatic, Energy Act Compliant Compartment Light Control with 3 & 4 way light switching capability
- Automatic data logging for help with HACCP reporting
- Local and remote notification of all alarm conditions

## **75LC Wireless Module**

The all new **75LC Wireless Module** provides wireless capability for the 75LC multi-monitor. Directly connected to and powered by the 75LC, the 75LC Wireless Module transmits data directly from the 75LC to the 75LC Communicator. The 75LC Wireless Module mounts onto the walk-in above the door (surface mount or flush mount in a single gang handi-box), and provides wireless capabillity for one or two 75LC's.


## **MS-1 Multi-Sensor**

The all new MS-1 multi-sensor is a standalone wireless module for monitoring other compartments and functions in your monitored environment such as reach-ins, under counter refrigerators and more. Available sensor types include temperature, humidity, contact opening (Example: Door Ajar) and contact closure (Example: Panic Alarm). MS-1 sensor configuration is field selectable to accept a variety of quantity and type of sensors depending on your application (Example: One MS-1 can accept up to 4 temperature sensors).



This document contains confidential information. The dissemination, publication, copying, or duplication of this document or the software described herein without prior written authorization is strictly prohibited.

## **MODULARM Model 75LC Communicator**



Report generated with web-based online viewer.

#### **SPECIFICATIONS**

#### **DIMENSIONS**

- 75LC Communicator: 10.25"W x 7"H x 2.75"D
- 75LC Wireless Module:
  SURFACE 2.75"W x 4.5"H x 2.25"D
  FLUSH Fits in single gang handi-box
- MS-1 multi-sensor:2.5"W x 2.5"H x .875"D,Mounting 3.5"W



#### Food Automation - Service Techniques, Inc.

905 Honeyspot Road, Stratford, CT 06615-7147 USA

Phone: **+1-203-377-4414**Sales: **1-800-327-8766**Fax: +1-203-377-8187

International Callers: +1-203-378-6860

#### www.KitchenBrains.com

Toll-free technical support 24/7 from the U.S., Canada, and Caribbean: **1-800-243-9271** 

# International offices are located in the United Kingdom, China and Singapore:

Europe, Middle East, Africa 31 Saffron Court Southfields Business Park Basildon, Essex SS15 6SS ENGLAND

Phone: +44 0 1268544000

China

1803, 18F, No 922 Hengshan Rd Shanghai 200030, CHINA Phone: **+8613916 854 613** 

Asia Pacific 13A MacKenzie Road 228676 Singapore Phone: +65 983159273

### WARRANTY

Kitchen Brains warrants that its products shall not fail to function in accordance with their specifications because of defects in material or workmanship, for the following warranty periods:

- New Products: New Products consisting of microprocessor based controllers, timers, data-loggers or remote monitoring devices for 1 year from date of purchase.
- ii. Sensors and Accessories: Sensors and accessories (consisting of probes, wireless sensors, hoses, relays, switches, mounting hardware or accessories) for 90 days from date of purchase.

For complete details consult www.kitchenbrains.com/ warranty

#### PATENTS

The products manufactured by Kitchen Brains are protected under one or more of the following U.S. Patents:

5,331,575	5,539,671	5,711,606	5,723,846
5,726,424	5,875,430	6,142,666	6,339,930
6,401,466	6,401,467	6,581,391	7,015,433
7,145,463	7,650,833	7,877,291	8,060,408
Plus foreign patents and patents pending. Plus licensed patent 5,973,297			

This document contains confidential information. The dissemination, publication, copying, or duplication of this document or the software described herein without prior written authorization is strictly prohibited.